EQUIPMENT

NEUMATIC ASPHIERIER





Simple! Reliable! Affordable!

CONTACT US





706-484-2253 info@basicequipment.net



www.basicequipment.net



The BASIC Model 700 Rubber Tire Roller is a tried and proven machine. It features a seven wheel design for greater compaction and easy maneuverability on small job sites. The 700 is ideally suited for commercial parking lots, driveways, and subdivision streets. The simplistic design promotes longer machine life, and allwheel independent oscillation ensures 100% surface contact, blending away seams and steel drum roller marks. The 700 provides consistent compaction across the work surface, minimizing the potential for potholes and costly warranty repairs.

Overall Dimensions:

Length: 112" Width: 51" Height: 74"

Wheel Base: 82"

Chassis Clearance: 9"

Weight:

1.5 to 3 Tons

Transmission:

Hydrostatic Drive: Chain

Tire Size:

8.5-15 6Ply

Powered By:

D1105 Kubota 24.8hp T4F Water Cooled Diesel Engine

Braking:

Drive Brake: Hydrostatic Parking Brake: Mechanical

Pressurized Water System:

Capacity: 70 gallons Removable Spray Tips

Steering:

Hydraulic power steering

Travel Speed:

0-6 Variable

Options:

Safety Beacon Work Lights Horn

Delu<u>xe Seat</u>

Aluminum Shade Canopy

Safety Features:

ISO Certified Folding ROPS 97 Decibel Back Up Alarm Neutral Safety Start

MANUFACTURED:



SCE, INC. RESERVES THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT NOTICE IN AN EFFORT TO IMPROVE PRODUCT QUALITY.

CONTACT US









